

## Pharmacy Refrigerators HYC-1378



### Ergonomic Design



High Accuracy  
Temperature Control



Interior  
LED



Lockable  
Design



### Five Alarm Functions

High/low temperature, power failure, sensor error,  
low battery, door ajar



### Adjustable Shelves

The shelves are adjustable to any height to  
fulfill different requirements



### Special Designed Slot for Sign Card

Adjustable shelves, the slot design be clear,  
store items is easy to distinguish



### Heated Double Pane Glass Door

Clear display of stored products without condensation  
at 32 °C and 85% relative humidity condition



### Self Closing Door

Energy conserving , maintains temperature  
uniformity to protect valuable samples

# Specifications

## HYC-1378

### Technical Data

|               |                      |    |    |
|---------------|----------------------|----|----|
| Cabinet Type  | Upright, double door |    |    |
| Climate Class | N                    |    |    |
| Cooling Type  | Forced air cooling   |    |    |
| Defrost Mode  | Auto                 |    |    |
| Refrigerant   | CFC-Free             |    |    |
| Noise((dB(A)) | 45                   | 45 | 48 |

### Performance

|                |     |  |  |
|----------------|-----|--|--|
| Temp Range(°C) | 2~8 |  |  |
|----------------|-----|--|--|

### Control

|            |                |  |  |
|------------|----------------|--|--|
| Controller | Microprocessor |  |  |
| Display    | LED            |  |  |

### Electrical Data

|                       |            |            |        |
|-----------------------|------------|------------|--------|
| Power Supply(V/Hz)    | 220-240/50 | 208~230/60 | 115/60 |
| Power(W)              | 800        | 800        | 950    |
| Electrical Current(A) | 4.2        | 4.2        | 11     |

### Dimensions

|                              |                                       |  |  |
|------------------------------|---------------------------------------|--|--|
| Capacity(L/Cu.Ft)            | 1378/48.7                             |  |  |
| Net/Gross Weight(approx)     | 310/360(kg) 683.4/793.7(lbs)          |  |  |
| Interior Dimensions(W*D*H)   | 1320*700*1500(mm) 52.0*27.6*59.1(in)  |  |  |
| Exterior Dimensions(W*D*H)   | 1440*925*1980(mm) 56.7*36.4*78.0(in)  |  |  |
| Packing Dimensions(W*D*H)    | 1570*1010*2120(mm) 61.8*39.8*83.5(in) |  |  |
| Container Load(20'/40'/40'H) | 6/12/12                               |  |  |



### Functions

|               |   |
|---------------|---|
| High/Low Temp | Y |
| Remote System | Y |
| Power Failure | Y |
| Sensor Error  | Y |
| Low Battery   | Y |
| Door Ajar     | Y |

### Accessories

|                 |          |
|-----------------|----------|
| Caster          | Y        |
| Foot            | Y        |
| Test Hole       | Y        |
| Shelves /Basket | 12/-     |
| USB Interface   | Y        |
| Temp Recorder   | Optional |

### Others

|             |    |
|-------------|----|
| Certificate | CE |
|-------------|----|

## Haier Medical and Laboratory Products Co., Ltd

Brand Building, Haier Industrial Park, No. 1  
Haier Road, Qingdao, 266101, P.R. China  
Tel: +86-0532-88936011 / 5955  
Website: www.haiermedical.com



Note: If slight difference occurs between pictures and actual products, please refer to actual products. Our company reserves the right of final interpretation to this brochure and please contact with us for further information you might need.

